



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*2708*00

Reason for extension:

SECTION I

0.1.	Make (trade name of manufacturer)	:	Monoflex	
0.2.	Type and general commercial description(s)	:	14.0105	RDW
0.3.	Means of identification of type marked on the component	:	Type approval number	
0.3.1.	Location of that marking	:	On type plate	
0.5.	Name and address of manufacturer	•	Monoflex AB Nibblegatan 21, Box 14 734 21 Hallstahammar S	sweden
0.7.	In the case of components and separate technica units, location and method of affixing of the EEC type approval mark	.l :	On type plate	• .
0.8.	Address(es) of assembly plant(s)	:	See information docume (annex III, item 0.8)	nt

Type-approval number: e4*94/20*2708*00

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76 8218 NX Lelystad

3. Date of test report : 24-01-2005

4. Number of test report : RDW-94/20-3653

5. Remarks (if any) : See Appendix I

6. Place : Zoetermeer

7. Date : 24-01-2005

8. Signature

J.P.M. Laumen

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I to EEC type-approval certificate No: e4*94/20*2708*00

concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1. Additional in	nformation
------------------	------------

1.1. Class of the type of coupling

: F

1.2. Categories or types of vehicles for which the device is designed or restricted

See fitting instructions

1.3. Maximum D-value

1.6.

10,90

kN

1.4. Maximum vertical load S at the coupling point:

85

kg

1.5 Maximum load U at the fifth wheel

Maximum V-value

ton

coupling point

kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

See fitting instructions



1.8 Information on the fitting of special towing brackets or mounting plates

See fitting instructions

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.