

## ECE TYPE-APPROVAL CERTIFICATE

Communication concerning the approval granted of a type of mechanical coupling device or component pursuant to Regulation No.55.



Approval No: <u>**E24** 55**R-010348</u>** Extension No: **N/A**</u>

Reason for extension: N/A 1. Trade name or mark of the device or component: SIARR - Westfalia - Monoflex 2. Manufacturer's name for the type of device or component: S1220 Non standard coupling ball 50, (detachable) 3. Manufacturer's name and address: S.I.A.R.R. Sas, Rue du General de Gaulle, F-76810 Luneray. If applicable, name and address of the manufacturers 4. representative: N/A 5. Alternative supplier's names or trade marks applied to the device or component: N/A 6. Name and address of the company or body taking responsibility for the conformity of production: S.I.A.R.R. Sas, Rue du General de Gaulle, F-76810 Luneray. 7. Submitted for approval on: Week 05-06, 2014 (dynamic) 14.06.2010 / 05.10.2010 (static) 8. Technical service responsible for conducting approval tests: TÜV SÜD Automotive GmbH, Westendstraße 199, D-80686 München, Germany. 9. Brief description 9.1 Type and class of device or component: *Type: SI220* Class: A50-X



Approval No: E24 55R-010348 Extension No: N/A

## 9.2 Characteristic values

9.2.1 Primary values
----------------------

D: 9.5 kN

Dc:

S: 75 kg

U: V:

Alternative values:

D: 9.5 kN

Dc:

S: 75 kg

U: V:

9.3 For Class A mechanical coupling devices or components, including towing brackets:

Vehicle manufacturer's maximum permissible vehicle mass:

2170 kg

Distribution of maximum permissible vehicle mass

between the axles:

Front: 1300 kg, Back: 900 kg

Vehicle manufacturer's maximum permissible towable

trailer mass:

1750 kg

Vehicle manufacturer's maximum permissible static mass

on coupling ball:

75 kg

Maximum mass of vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied)but not including driver:

1300 kg

Loading condition under which the tow ball height of a mechanical coupling device fitted to category M1 vehicles is to be measured – see paragraph 2 of annex 7, appendix 1:

Dimensions given by the vehicle manufacturer.

9.4 For class B coupling heads, is the coupling head intended to be fitted to an unbraked O1 trailer: (yes/no)

N/A

10. Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points given by the manufacturer

See manufacturer's documentation.

11. Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component:

See manufacturer's documentation.



Approval No: <u>E24 55R-010348</u> Extension No: *N/A* 

12.	Additional information where the use of coupling device or
	component is restricted to special types of vehicles
	- see annex 5, paragraph 3.4:

See manufacturer's documentation.

13. For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type:

N/A

14. Date of test report:

26.02.2014

15. Number of test report:

14-00091-CX-GBM-00

16. Approval mark position:

Manufacturer's plate on socket plate,

riveted.

17. Reason(s) for extension of approval:

N/A

Approval granted/extended/refused/withdrawn:

Granted

19: Place:

Dublin

20. Date:

18.

13th March, 2014.

21. Signature:



22. The list of documents deposited with the Administration Service which has granted approval is annexed to this communication and may be obtained on request.