



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*1998*00

Reason for extension:

SECTION I

0.1. Make (trade name of manufacturer) : Monoflex

0.2. Type and general commercial description(s) : 13.0021 Monoflex/ACS

0.3. Means of identification of type marked on the : Type approval number component

0.3.1. Location of that marking : On type plate


0.5. Name and address of manufacturer : Monoflex AB
Nibblegatan 21, Box 14

734 21 Hallstahammar Sweden

0.7. In the case of components and separate technical: On type plate units, location and method of

0.8. Address(es) of assembly plant(s) : See information document

(annex III, item 0.8)



Europaweg 205 Zoetermeer

affixing of the EEC type approval mark

Phone +31 79 3458143 Fax +31 79 3458043



Type-approval number: e4*94/20*1998*00

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76

8218 NX Lelystad

3. Date of test report

: 03-01-2002

4. Number of test report

: RDW-94/20-1798

5. Remarks (if any)

: See Appendix I

6. Place

: Zoetermeer

7. Date

: 03-01-2002

8. Signature

pW /

J.P.M. Laumen

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No : e4*94/20*1998*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1.	Additional information				
1.1.	Class of the type of coupling	:	F		
1.2.	Categories or types of vehicles for which the device is designed or restricted	:	See fitting instructions		
1.3.	Maximum D-value	:	10,28		kN
1.4.	Maximum vertical load S at the coupling point	:	80	kg	
1.5	Maximum load U at the fifth wheel	:	· 	ton	
1.6.	coupling point Maximum V-value	:		kN	
1.7.	Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles	:	See fitting instructions		
1.8	Information on the fitting of special towing brackets or mounting plates	:	See fitting instr	ructions	

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.

