



Vehicle Certification Agency

THE UNITED KINGDOM VEHICLE APPROVAL AUTHORITY

COMMUNICATION CONCERNING THE APPROVAL GRANTED ⁽¹⁾/ ~~APPROVAL EXTENDED ⁽¹⁾/ APPROVAL REFUSED ⁽¹⁾/ APPROVAL WITHDRAWN ⁽¹⁾/ PRODUCTION DEFINITELY DISCONTINUED ⁽¹⁾~~ OF A TYPE OF MECHANICAL COUPLING DEVICE OR COMPONENT, PURSUANT TO REGULATION NO 55.01



Approval No: E11*55R01/06*11737*00

1. Trade name or mark of the device or component: C P Witter Ltd (Horizon Global UK)

2. Manufacturer's name for the type of device or component: VW99 Fixed Flange neck
VW99Q Detachable Swan neck
VW99QF Detachable Swan neck
VW99S Fixed Swan neck
322075600001 Detachable Swan neck
322076600001 Fixed Swan neck

VW T Cross SUV (12/2018>)

3. Manufacturer's name and address:
C P Witter Ltd (Horizon Global UK)
Drome Road
Deeside Industrial Park
Deeside
Flintshire
CH5 2NY
United Kingdom

4. If applicable, name and address of the manufacturer's representative: Not applicable

5. Alternative supplier's names or trade marks applied to the device or component:
Trimas Corporation, Horizon Global, Trimotive, BTM, Kovil, Hayman Reese, Parkside, Pro Series, Reese, Tow Ready, Draw-Tite, Hidden Hitch, PF Jones, TrailBoss, Westfalia Automotive, Witter Towbars.

6. Name and address of company or body taking responsibility for the conformity of production:
C P Witter Ltd (Horizon Global UK)
Drome Road
Deeside Industrial Park
Deeside
Flintshire
CH5 2NY
United Kingdom

7. Submitted for approval on: 06 December 2019
8. Technical service responsible for conducting approval tests: Vehicle Certification Agency

9. Brief description:

9.1. Type and class of device or component: A50-X

9.2. Characteristic values:

9.2.1. Primary values:

D:	7.9 kN	Dc:	7.9 kN	S:	70 kg
U:	0.0 tonnes	V:	N/A kN		

Alternative Values

D:	N/A kN	Dc:	N/A kN	S:	N/A kg
U:	N/A tonnes	V:	N/A kN		

9.3. For Class A mechanical coupling devices or components, including towing brackets:

Vehicle manufacturer's maximum permissible vehicle mass: 1900 kg

Distribution of maximum permissible vehicle mass between the axles:

Axle 1:	1010 kg	Axle 2:	900 kg
Axle 3:	Not Applicable kg	Axle 4:	Not Applicable kg

Vehicle manufacturer's maximum permissible towable trailer mass: 1400 kg

Vehicle manufacturer's maximum permissible static mass on coupling ball: 70 kg

Maximum mass of the vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied) but not including driver: 1310 kg

Loading condition under which the tow ball height of a mechanical coupling device fitted to category M₁ vehicles is to be measured -see paragraph 2 of annex 7, appendix 1:


Each row 2x68kg + 2x7kg luggage

9.4. For class B coupling heads, is the coupling head intended to be fitted to an unbraked O1 trailer: Not applicable

10. Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points (see Annex 2, Appendix 1) given by the vehicle manufacturer: See Manufacturer's Documents

11. Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component (see Annex 2, Appendix 1): Not applicable

VSV470439

12. Additional information where the use of the coupling device or component is restricted to special types of vehicles - see annex 5, paragraph 3.4. Not applicable
13. For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type: Not applicable
14. Date of test report: 17 December 2019
15. Number of test report: VSV470439
16. Approval mark position: See Manufacturer's Documents
17. Reason(s) for extension of approval: Not applicable
18. Approval: GRANTED / ~~EXTENDED~~ / ~~REFUSED~~ / ~~WITHDRAWN~~
19. Place: BRISTOL
20. Date: 20 DECEMBER 2019
21. Signature:  D. LAWLOR
Chief Technical and Statutory Operations Officer
22. The list of documents deposited with the Administration Service which has granted approval is annexed to this communication and may be obtained on request.

Any remarks: None

VSV470439